

Temperature range -20 °C to +100 °C
Pore-free plastic surface, double-walled, tightly welded



thermoport® "Maxi K" for banquet solutions, plastic

2 x thermoport® with pore-free plastic surface, non-detachable, with casters (dia. 125 mm) mounted to bottom thermoport®. Deep-drawn version.

Suitable for transporting hot and cold food in GN containers and loading with stainless steel GN 2/1 grilles.

Type 6000 KB: Heatable, max. achievable temperature +90 °C, heating output 380 W, rated voltage 1 N AC 230 V 50 Hz.



Frontloader



Frontloader

Type	2 x 6000 K (unheated), mobile	1 x 6000 K (unheated), 1 x 6000 KB (heated), mobile
Capacity with GN containers	max. 2 x 104 litres	max. 2 x 104 litres
External dimensions L x W x H in mm	766 x 779 x 1280	766 x 790 x 1280
Overall weight	56.5 kg	59.7 kg
Loading examples	8 x GN 1/1, 200 mm, etc.	8 x GN 1/1, 200 mm, etc.
Order no.	85 02 08 02 orange 85 02 08 12 black	85 02 08 04 orange 85 02 08 07 black

Accessories

Grille, GN 2/1, stainless steel, light version Order no.	84 14 01 06	84 14 01 06
Insulated divider for type 6000 K, unheated Order no.	85 02 20 12 orange 85 02 20 69 black	85 02 20 12 orange (for type 6000 K) 85 02 20 69 black (for type 6000 K)
Cooling plate GN 1/1, plastic for type 6000 K, unheated Order no.	85 02 20 38 orange 85 02 20 67 black	85 02 20 38 orange (for type 6000 K) 85 02 20 67 black (for type 6000 K)
Insert frame with one long support for GN 4 x 1/4, 6 x 1/6 or 2 x 2/4 Order no.	85 01 20 09	85 01 20 09
Insert frame with 2 cross-supports for GN 9 x 1/9 or 6 x 1/6 Order no.	85 01 20 10	85 01 20 10
Tray frame 6000, stainless steel for inserts sized 600 x 400 mm, 8 pairs of shelf rail supports Order no.	85 02 20 44	85 02 20 44