

# thermoport® –

## REGNERATING, TRANSPORTING AND SERVING FOOD – WITH GENERATION 2.0

The classics. Made from light, robust and pore-free plastic – double-walled and tightly welded. The thermoport® is available in various versions: heated or unheated, orange or black, toploader or frontloader, so you can find the right thermoport® for the job.

Generation 2.0 is equipped with more powerful heaters and additional special features.

### BENEFITS AT A GLANCE:



Reliable storage.



Safe transport.



Easy serving.



Several temperature zones via insulated dividers.



The original.



Perfect insulation.



Digital heating.



Dishwasher-safe.  
(with heating system removed)



Low weight.



Robust.



#### thermoport® 10

Food transport box with pore-free plastic skin, double-wall welded, high-quality snap locks, dishwasher-safe, range of application: -20 to +100 °C

L x W x H (mm):  
380 x 220 x 153

Weight: 1.8 kg

Max. filling volume: 2.7 l

#### thermoport® 10:

85 02 01 01 orange (without equipment)

85 02 01 04 black (without equipment)

#### thermoport® 2.0 50 KB-CNS / 50 KB / 50 K

Food transport box with pore-free plastic skin, double-wall welded, high-quality snap locks, dishwasher-safe, range of application: -40 to +100 °C.

**thermoport® 2.0 50 KB-CNS:** with stainless steel interior casing for direct food transport.

The temperature of up to 100 °C is reached even quicker via the new foil heating.

L x W x H (mm):  
370 x 645 x 240

Weight: 8 kg / 7.3 kg / 6.9 kg

Max. filling volume: 11.7 l

Heating power (KB models): 500 W

🔥 **thermoport® 2.0 50 KB-CNS:**

85 02 02 18 orange

🔥 **thermoport® 50 KB:**

85 02 02 06 orange

85 02 02 17 black

#### thermoport® 50 K:

85 02 02 01 orange

85 02 02 16 black

#### thermoport® 2.0 100 KB-CNS / 100 KB / 100 K

Food transport box with pore-free plastic skin, double-wall welded, high-quality snap locks, dishwasher-safe, range of application: -20 to +100 °C.

**thermoport® 2.0 100 KB-CNS:** with stainless steel interior casing for direct food transport.

The temperature of up to 100 °C is reached even quicker via the new foil heating.

L x W x H (mm):  
370 x 645 x 308

Weight: 10 kg / 8.3 kg / 7.2 kg

Max. filling volume: 26 l

Heating power (KB models): 500 W

🔥 **thermoport® 2.0 100 KB-CNS:**

85 02 03 52 orange

🔥 **thermoport® 100 KB:**

85 02 03 13 orange

85 02 03 29 black












#### thermoport® 100 K:

85 02 03 01 orange

85 02 03 28 black



## DIMENSIONS:


										
50 K/50 KB 11.7 l	75 light 18.4 l	100 K/100 KB 26 l	600 K/600 KB 33 l	1000 K/1000 KB 52 l	6000 K/6000 KB 104 l	50 11.7 l	230 K 15.3 l	100-K-UNI 26 l	500-KB-UNI 26 l	1000 K-UNIT / KB-UNIT 52 l



### thermoport® 600 KB/600 K

Food transport box with pore-free plastic skin, double-wall welded, high-quality snap locks, dishwasher-safe, range of application: -20 to +100 °C, max. attainable temperature: +95 °C

L x W x H (mm):  
420 x 645 x 390 / 420 x 610 x 386  
Weight: 11 kg / 9.2 kg  
Max. filling volume: 33 l  
Heating power (KB models): 240 W

 **thermoport® 600 KB:**  
85 02 05 07 orange  
85 02 05 17 black

**thermoport® 600 K:**  
85 02 05 05 orange  
85 02 05 18 black

### thermoport® 2.0 1000 KB / 1000 K

Food transport box with pore-free plastic skin, double-wall welded, high-quality snap locks, dishwasher-safe, range of application: -20 to +100 °C.  
**Thermoport 2.0 1000 KB:** heatable with digital, more powerful circulating air heating, max. attainable temperature: +85 °C.

L x W x H (mm):  
435 x 670 x 561 / 435 x 610 x 561  
Weight: 17.2 kg / 12 kg  
Max. filling volume: 52 l  
Heating power (KB models): 763 W

 **thermoport® 2.0 1000 KB:**  
85 02 04 23 orange  
85 02 04 24 black

**thermoport® 1000 K:**  
85 02 04 01 orange  
85 02 04 12 black

### thermoport® 6000 KB/6000 K

Food transport box with pore-free plastic skin, double-wall welded, high-quality snap locks, dishwasher-safe, range of application: -20 to +100 °C, max. attainable temperature: +95 °C

L x W x H (mm):  
645 x 790 x 560  
Weight: 23 kg / 21 kg  
Max. filling volume: 104 l  
Heating power (KB models): 300 W

 **thermoport® 6000 KB:**  
85 02 08 03 orange  
85 02 08 06 black

**thermoport® 6000 K:**  
85 02 08 01 orange  
85 02 08 05 black