



**The new range of Kronen blenders:
in beautiful stainless steel!**

**Quality and high performance –
excellent results everytime!**



Choose the Kronen blender for long-life-performance. Every part is of high quality made in Germany and Switzerland. And cause there is nothing better- machine housing in robust stainless steel.

For example the KM-4 S with continuous, variable speed setting up to 15.000 r.p.m.



Unsurpassed technical performance in kitchen and bar! Easy and simple to use. Consistently good results.



Choose between 4 table top models:
The customer-programmable model with 6 speeds / 12 programmes or the KM-4 S with continuously variable speed up to 15.000 r.p.s.

Or the model with 3 fixed speeds 3.500 – 13.500 r.p.m.
Easy to handle per kip switch.
Available as single or double model.

**Perfect drinks –
easy work with
Kronen appliances!**



**Whip up perfect results
in no time!
Produces stable and
perfect foam even with
soups and sauces.**



The KM-4 PE to integrate in a juice bar or service counter. Installation-Kit in hygienic stainless steel. 6 speeds or 12 programmes.



Producing large amount of smoothies in your supermarket or juices in the Juice Bar – the Kronen blender is exactly the right choice!

... or the KM-4 P 6 speeds or 12 adjustable settings. Perfect for franchise restaurants.

But most important:
The results!
For whisking, blending and mashing,
mixing and stirring.
Kronen blenders set standards –
worldwide!





Space saving and practical – stackable jars available for 2 or 4 liters in polycarbonate or in robust stainless steel.



Our special blades on hardened stainless steel ball bearings guarantee long lasting and unsurpassed mixing qualities.
Easy to change, with stand high and low temperatures.
Stand CC blades (right) and FD (left) for excellent whisking performance.

Technical data:

Electrical supply	230 V / 4.2 A +- 6% 48...62 Hz, sinusoidal, interference free
Power	900 W max. (continuous use)
Motor	High temperature commutator motor with fan
Motor control	Soft start Model KM-4 B: 3 speed (3.500, 8.700 & 13.500 r.p.m.) with electronically controlled rotational speed Model KM-4 S: continuously variable speed up to 15.000 r.p.m.. Thermal cut out and electronic monitoring devices. Model KM-4P: 6 speeds or 12 programs.
Electrical features	Safety control for lid, complies with EN 60335-1; electromagnetic compatibility in compliance with EMV regulation
Design features	Motor base unit from stainless steel, blades from surgical stainless steel
Weight	6kg, base only
Noise emission	Less than 70 dBA in normal use

Dimensions

